

Google

same call includes transaction identifier rollback

Search

Advanced Search
Preferences

Web Results 1 - 10 of about 292,000 for same call includes transaction identifier rollback. (0.28 seconds)

net.sourceforge.hivetrans.transaction (HiveMind Utilities API ...

The configuration for the interceptor includes the transaction demarcation to be ... way- the conditions of transaction rollback when an exception is thrown ...

hivetrans.sourceforge.net/.../net/sourceforge/hivetrans/transaction/package-summary.html

- 20k - [Cached](#) - [Similar pages](#)

The ECI request

TPNName: The transaction ID of a CICS mirror program. ... When the user application makes an ECI commit or rollback call, the CICS server attempts to commit ...

publib.boulder.ibm.com/infocenter/cicsts/v2r2/topic/com.ibm.cicsuc600.doc/cclao0214.htm

- 11k - [Cached](#) - [Similar pages](#)

Heterogeneous operations with differing transaction protocols - US ...

This call includes the transaction id (Xid) that was received with the In either of these cases the Transaction Manager 120 issues a rollback call. ...

www.patentsform.us/patents/5852732-description.html - 39k - [Cached](#) - [Similar pages](#)

Method for managing subpage concurrency control and partial ...

Since a transaction includes execution of an application-specified back the transaction to its beginning (with a call like rollback(0,transid), ...

www.freepatentsonline.com/EP0295424.html - 66k - [Cached](#) - [Similar pages](#)

Distributed Transactions

Every transaction branch has a unique transaction ID, but transaction to the same resource manager (database), call the isSameRM() method from one XA ...

www.comp.hkbu.edu.hk/docs/oracle8i/java.816/a81354/xadistr2.htm - 32k -

[Cached](#) - [Similar pages](#)

Distributed Transactions

Each ID includes a transaction branch ID component and a distributed instances correspond to the same resource manager (database), call the isSameRM() ...

www.stanford.edu/dept/itss/docs/oracle/9i/java.920/a96654/xadistra.htm - 80k -

[Cached](#) - [Similar pages](#)

29 Distributed Transactions

Each ID includes a transaction branch ID component and a distributed transaction ID ... In the GLOBAL_TXN mode, applications must not call commit , rollback ...

www.filibeto.org/sun/lib/nonsun/oracle/10.2.0.1.0/B19306_01/java.102/b14355/xadistra.htm -

- 78k - [Cached](#) - [Similar pages](#)

MySQL :: MySQL Search

SAVEPOINT and ROLLBACK TO SAVEPOINT Syntax SAVEPOINT identifier ROLLBACK [WORK] TO ... If the current transaction has a savepoint with the same name, ...

dev.mysql.com/doc/mysql/search.php?q=transactional - 22k - [Cached](#) - [Similar pages](#)

Cache and JTA Transactions - GemFire Developer - GemFire ...

The EntryEvent that the callbacks receive has a unique transaction ID, ... the JTA transaction manager to call methods like commit and rollback on the ...

developer.gemstone.com/display/gfedev/Cache+and+JTA+Transactions - 31k -

[Cached](#) - [Similar pages](#)

WebLogic Tuxedo Connector JATMI Transactions

A transaction is terminated by a call to commit() , rollback() , or ... does not guarantee that all calls for a particular transaction Id are routed to a ...

edocs.bea.com/wls/docs92/wtc_atmi/Transactions.html - 46k - [Cached](#) - [Similar pages](#)

[1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [Next](#)

same call includes transaction identifier rollback

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#) | [Try Google Experimental](#)

©2008 Google - [Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)